



- Material: high quality alloy steel.
- Surface treatment: self-color, polishing, blackened, painted, plastic coating, electric galvanized, hot-dip galvanized, etc.
- Manufacture standard: ISO, DIN, BS, JIS, ASTM.
- Quality grade: G80.
- Safety factor: min.4
- Non-standard chain according to the clients requirements.

G80 Lifting Chain

Chain Size (mm)	Width (mm)		W.L.L (t)	Test Load (KN)	Min Breaking Load (KN)	Weight (kg/m)
	Inside min.	Outside min.				
5x15	6	17	0.75	18	31.4	0.54
6x18	7.5	21	1.1	27	45.2	0.79
7.1x21	9	24.5	1.5	37	61.6	1.07
8x24	10	28	2	48	80.4	1.38
9x27	11	30	2.5	63.3	102	1.75
10x30	12.5	35	3.2	76	125	2.2
11.2x34	12.6	36.5	3.8	92	154	2.33
12x36	15	42	4.6	109	181	3.1
13x39	16.3	46	5	128	214	3.8
14x42	18	49	6.3	150	250	4.13
14x50	17	48	6.3	150	250	4
15x46	20	52	7	168	280	5.17
16x48	20	56	8	192	320	5.63
16x49	24.5	59.5	8	192	320	5.71
16x64	23.9	58.9	8	192	320	5.11
18x54	23	63	10	246	410	6.85
18x64	21	60	10	246	410	6.6
19x57	23.7	63.2	11.3	270	450	7.7
20x60	25	70	12.5	300	450	8.6
22x65	28	74.2	15.3	366	610	10.7
22x66	28	77	15.3	366	610	10.2
22x86	26	74	15.3	366	610	9.5
24x72	32	82	18	432	720	12.78
24x86	28	79	18	432	720	11.6
26x78	35	91	21.3	510	850	14.87
26x92	30	86	21.3	510	850	13.7
30x90	38	105	28.3	678	1130	19.6
30x108	34	98	28.3	678	1130	18
32x96	40	106	32.2	772	1286	22.29
34x126	38	109	36.3	870	1450	22.7
34x102	46.5	121.5	36.3	870	1450	25.5
36x108	49.5	128.5	40.7	978	1630	31
38x137	42	121	45.3	1086	1810	29
38x114	52	136	45.3	1086	1810	32
42x126	55.5	144.5	55.4	1332	2200	38.6