

Crosby® Forged Hooks



SEE APPLICATION AND WARNING INFORMATION


Para Español: www.thecrosbygroup.com

On Pages 140-141

S-3316



- Easily attaches to any chain and electric hoist with welded link load chain, roller chain or wire rope with suitable end fitting.
- Swivel jaw is forged.
- Suitable for infrequent, non-continuous rotation under load.
- Use in corrosive environment requires shank and nut inspection in accordance with ASME B30.10-1.10.4(b)(5)(c)2009.



S-3316 Replacement Hook

| Working Load Limit (Tons)* | Frame Code | S-3316 Stock No. | Weight Each (lbs.) | Dimensions (in.) | | | | | | | | | | Replacement Latch Kit Stock No. |
|----------------------------|------------|------------------|--------------------|------------------|------|-----|------|-----|------|------|------|------|------|---------------------------------|
| | | | | A | B | C | D | H | L | O | P | R | T | |
| 1/2 | F | 1023029 | 1.25 | 1.31 | .76 | .56 | 3.19 | .38 | 6.12 | .97 | 2.25 | 4.59 | .81 | 1096374 |
| 1 | H | 1023047 | 2.61 | 1.56 | 1.00 | .69 | 4.09 | .44 | 7.69 | 1.12 | 2.84 | 5.81 | 1.19 | 1096468 |

*Ultimate Load is 5 times the Working Load Limit.



A-378



- Forged Alloy Steel - Quenched and Tempered.
- Deep straight throat permits efficient handling of flat plates or large cylindrical shapes.

A-378 Sorting Hook

| Working Load Limit at tip of Hook (Tons)* | Working Load Limit at bottom of Hook (Tons)* | A-378 Stock No. | Style | Weight Each (lbs.) | Dimensions (in.) | | | |
|---|--|-----------------|-------------|--------------------|------------------|----------------|------------------------|--------------------------|
| | | | | | I.D. of Eye | Overall Length | Opening at top of Hook | Radius at bottom of Hook |
| 2 | 7-1/2 | 1028024 | No Handle | 6.42 | 1.38 | 9.69 | 2.81 | .625 |
| 2 | 7-1/2 | 1028033 | With Handle | 6.42 | 1.38 | 9.69 | 2.81 | .625 |

*Ultimate Load is 4 times the Working Load Limit.

Hooks & Swivels