




H-330 / A-330



- Forged Steel - Quenched and Tempered.
- Design factor is 4:1.
- Features quick and easy assembly.
- H-330 designed for Crosby Spectrum 4® chain.
- A-330 designed for Crosby Spectrum 7® chain.



H-330 / A-330 Clevis Grab Hooks

Chain Size (mm)	Stock No.		Working Load Limit (t)		Weight Each (kg)	Dimensions (mm)											
	H-330 Carbon	A-330 Alloy*	H-330 Carbon	A-330 Alloy		A	B	C	D	E	G	H	K	L	N	P	R
7	1027105	1027249*	1.18	1.59	.16	25.4	8.15	7.85	46.0	8.65	22.4	18.3	11.9	77.5	44.5	7.85	41.7
8	1027123	1027267*	1.77	2.04	.29	30.2	9.90	9.15	54.0	11.2	24.6	23.1	15.0	93.0	52.5	9.65	61.5
10	1027141	1027285*	2.45	3.22	.45	35.1	11.4	11.4	64.5	12.7	29.7	25.4	18.3	109	59.5	11.2	61.0
11	1027169	1027301	3.27	4.54	.59	42.2	16.8	15.7	78.5	14.2	33.3	28.7	17.5	125	67.5	14.2	70.0
13	1027187	1027329*	4.17	5.44	.95	47.8	14.5	17.8	90.5	16.8	38.9	31.8	19.8	145	75.5	16.0	81.0
16	1027203	1027347	5.90	8.2	1.91	58.0	23.1	21.3	112	19.8	45.2	39.6	27.7	179	109	19.1	104
19	1027221	1027365	9.16	11.2	2.95	66.5	23.9	23.9	133	23.9	54.0	47.8	33.3	207	129	22.4	118

* These A-330 hooks are forged with an "8" designating Grade 80, and are suitable for use with Grade 8 chain in over head lifting applications as long as hook is proof-tested as part of the chain sling assembly or as an individual component per ASME B30.9. We recommend the use of the A-338 which is proof tested and supplied with a proof test certificate.

Contact Us:



WHATSAPP

0857-7730-4523



CALL

(021) 691 9595