


SOLIDO Eye Sling Hooks with forged Safety Latch

The grade 80 eye sling hooks TWN 0858/1 are used to assemble standard chain slings. The lifting chains are assembled by using connecting links, e.g. THI-LOK®s TWN 1320. The forged safety latch prevents an unintentional detachment from the load. The sling hooks comply with the DIN EN 1677-2.

TWN 0858/1



Trade Size	Article-No.	Working Load Limit [t]	Dimensions [mm]							Weight app. [kgs]
			e	d ₁	d ₂	g	h	c	f	
6-8	F329010 ¹⁾	1,12	92	21	11	20	20	17	-	0,36
7/8-8	F329110 ¹⁾	2,00	118	28	14	27	25	20	-	0,76
10-8	F329210 ¹⁾	3,15	146	36	18	34	32	29	-	1,50
13-8	F329310 ¹⁾	5,30	168	42	21	41	41	35	-	2,55
16-8	F329410 ¹⁾	8,00	210	54	25	48	50	41	-	4,65
18/20-8	F329510 ¹⁾	12,50	244	58	27	59	59	51	-	7,60
22-8	F329710 ¹⁾	15,00	271	65	30	68	62	55	-	10,20
26-8	F329810	21,20	302	70	33	74	71	60	81	15,00
32-8	F329910	31,50	350	80	38	90	84	70	99	24,30

¹⁾ With circular eyelet

Contact Us:



WHATSAPP

0857-7730-4523



CALL

(021) 691 9595