


TWN 1815



Master Link Assemblies for 3- and 4-leg Rope Slings

The grade 100 master link assemblies TWN 1815 are used to assemble 3- and 4-leg wire rope slings. The extra large intermediate links enable an easy assembly of wire rope slings. The manufacturing and testing requirements are based on the DIN EN 1677 parts 1 and 4, under consideration of grade 100 load capacities. The dimensions comply with the DIN 5688-3.

SAFETY
4 : 1

DGUV
ZERT

Article-No.	Working Load Limit $0^\circ < \beta \leq 45^\circ$ [t]	Dimensions [mm]							Classification ¹⁾ of the Wire Rope Diameter*		Weight app. [kgs]
		d ₁	t ₁	b ₁	e	d ₂	t ₂	b ₂	Fiber [mm]	Steel [mm]	
F1815016	3,50	16	110	60	200	13	90	50	12	11	1,11
F1815018	5,00	18	130	70	240	16	110	60	14	14	1,85
F1815022	6,60	22	160	90	290	18	130	70	16	16	3,08
F1815026	9,30	26	150	100	340	22	160	90	20	18	5,40
F1815032	13,90	32	230	125	410	26	180	100	24	22	9,10
F1815036	20,00	36	250	140	480	32	230	125	28	28	15,00
F1815045	26,30	45	320	175	540	36	250	140	32	32	24,40
F1815050	40,00	50	340	190	660	45	320	175	40	40	40,40

*Acc. to the DIN EN 13414-1

¹⁾ The classification for use in the 3 / 4 strand takes into account an angle of inclination of $0^\circ < \beta \leq 45^\circ$.

Contact Us:



WHATSAPP

0857-7730-4523



CALL

(021) 691 9595