



Suspension Components

THIELE Components of the GK8 Assembly System have a Safety Factor of 4.
 The Components comply with all present standards like EN 818, EN 1677 and DIN 5688-3.

Dimension	Art.-No.	Working Load Limit [t]	Dimensions [mm]						Weight app. [kgs]	TWN 0795
			D	F	B					
B 8	F122880	1,12	8	36	18				0,05	
B 10	F122890	2,00	10	46	23				0,09	
B 13	F122930	3,15	13	60	30				0,20	
B 16	F122970	5,30	16	70	35				0,36	
B 20	F123030	8,00	20	90	45				0,73	
B 22	F123070	10,00	22	100	50				0,97	
B 26	F123090	12,50	26	120	60				1,60	
B 28	F123190	15,00	28	130	65				1,90	
B 32	F123110	21,20	32	140	70				2,90	
B 36	F123130	25,00	36	160	80				4,20	
B 40	F123150	31,50	40	180	90				5,80	
B 45	F123170	40,00	45	200	100				8,20	
B 50	F123210	50,00	50	220	110				11,00	
B 56	F123230	63,00	56	260	130				16,00	
B 63	F123270	80,00	63	280	140				22,00	
B 70	F123290	100,00	70	320	160				31,00	
B 80	F123300	125,00	80	360	180				46,50	
B 90	F123320	160,00	90	400	200				65,50	



Intermediate Master Link
 Type B
 according to DIN 5688-3