




Suspension Components

THIELE Components of the GK8 Assembly System have a Safety Factor of 4.
 The Components comply with all present standards like EN 818, EN 1677 and DIN 5688-3.

Art.-No.	Working L. L. $\beta = 0^\circ - 45^\circ$ [t] SF= 1:4	Dimensions [mm]							Weight app. [kgs]	Categorization of the wire rope diameter*		TWN 0796
		E	D	F	B	D ₁	F ₁	B ₁		Fiber Rope [mm]	Steel Rope [mm]	
F0796016	2,80	200	16	110	60	13	90	50	1,20	11,00	10,00	 <p>Master Link Assembly for 3 and 4 Leg Wire Rope EN 13414-1</p>
F0796018	4,00	240	18	130	70	16	110	60	1,90	13,00	12,00	
F0796022	5,30	290	22	160	90	18	130	70	3,10	14,00	14,00	
F0796026	7,50	340	26	180	100	22	160	90	5,40	18,00	16,00	
F0796032	11,10	410	32	230	125	26	180	100	9,10	22,00	20,00	
F0796036	16,00	480	36	250	140	32	230	125	15,10	26,00	24,00	
F0796045	21,00	570	45	320	175	36	250	140	25,00	28,00	28,00	
F0796050	31,60	660	50	340	190	45	320	175	42,00	36,00	36,00	
F0796056	40,20	720	56	380	210	50	340	190	57,00	40,00	40,00	
F0796063	50,10	810	63	430	240	56	380	210	79,00	44,00	44,00	
F0796085	101,80	1040	85	520	290	80	520	290	202,00	60,00	60,00	

*according to DIN EN 13414-1 for 3/4 leg slings