


Compound Rope

Structure



Fiber Content
 Wire Strand

Characteristics

- Good anti-corrosion
- Easier to set up
- Easy Handling

Applications

- Trawl
- Tie-up lines
- Other industries



| Size | | Kuralon | PP |
|-----------------|----------|------------------|---------|
| Wire Strand Dia | Rope Dia | Wire Strand 1×24 | |
| mm | mm | kg/200m | kg/200m |
| 2.00 | 16 | 52 | 47 |
| 2.67 | 18 | 73 | 68 |
| 3.33 | 20 | 103 | 92 |
| 4.00 | 22 | 138 | 124 |
| 4.67 | 24 | 179 | 164 |
| 5.33 | 26 | 225 | 210 |
| 6.00 | 28 | 275 | 261 |
| 6.67 | 30 | 333 | 317 |
| 7.33 | 32 | 393 | 376 |
| 8.00 | 34 | 457 | 439 |
| 8.00 | 36 | 483 | 445 |
| 8.67 | 36 | 530 | 511 |
| 8.00 | 38 | 503 | 450 |
| 8.67 | 38 | 550 | 518 |
| 8.00 | 40 | 523 | 460 |
| 8.67 | 40 | 570 | 528 |
| 8.00 | 42 | 543 | 470 |
| 8.67 | 42 | 590 | 536 |
| 8.00 | 45 | 563 | 485 |
| 8.67 | 45 | 610 | 552 |
| 8.00 | 50 | 583 | 505 |
| 8.67 | 50 | 630 | 580 |

| Size | | PP | |
|-----------------|----------|------------------|------------------|
| Wire Strand Dia | Rope Dia | Wire Strand 1×12 | Wire Strand 1×24 |
| mm | mm | kg/500m | kg/500m |
| 3.00 | 22 | 199 | 223 |
| 3.33 | 22 | 221 | 251 |
| 4.00 | 22 | 273 | 315 |
| 4.67 | 22 | 333 | 391 |
| 5.33 | 22 | 404 | 479 |
| 3.33 | 24 | 241 | 271 |
| 4.00 | 24 | 293 | 335 |
| 4.67 | 24 | 353 | 411 |
| 5.33 | 24 | 424 | 499 |
| 4.00 | 26 | 314 | 356 |
| 4.67 | 26 | 374 | 432 |
| 5.33 | 26 | 445 | 521 |
| 4.00 | 28 | 337 | 379 |
| 4.67 | 28 | 407 | 455 |
| 5.33 | 28 | 468 | 543 |
| 6.00 | 28 | 544 | 641 |
| 6.67 | 28 | 631 | 751 |
| 4.00 | 30 | 361 | 403 |
| 4.67 | 30 | 421 | 479 |
| 5.33 | 30 | 492 | 568 |
| 6.00 | 30 | 568 | 666 |
| 6.67 | 30 | 655 | 775 |