




Mega NY

Structure



8-STRAND CONSTRUCTION

Fiber Content

- Nylon Fiber

Characteristics

- Well balanced construction
- High strength
- Excellent wear life
- Fast, easy splicing

Applications

- Mooring lines
- Shock and tow lines
- Mooring pendants
- Anchor lines

Dia		Cir	Weight		MBL	
inch	mm	inch	200m/kg	600ft/lb	ton	kN
1-1/8	28	3-1/2	95.3	192	18.00	176.50
1-1/4	32	4	123	248	23.00	225.60
1-7/16	36	4-1/2	155	313	29.00	284.40
1-9/16	40	5	191	385	35.00	343.20
1-3/4	44	5-1/2	234	470	42.00	411.90
1-7/8	48	6	277	558	48.50	475.60
2-1/16	52	6-1/2	328	661	56.50	554.10
2-1/4	56	7	380	766	64.00	627.60
2-3/8	60	7-1/2	438	883	72.00	706.10
2-1/2	64	8	498	1,002	82.50	809.10
2-7/8	72	9	631	1,270	102.00	1,000.30
3-5/32	80	10	777	1,566	125.00	1,225.80
3-7/16	88	11	937	1,889	148.00	1,451.40
3-13/16	96	12	1103	2,224	173.00	1,696.50
4-1/8	104	13	1298	2,627	205.00	2,010.40
4-7/16	112	14	1505	3,034	225.00	2,206.50

• ± 5% tolerance according to ISO 2307

