




Mega PP

Structure



8-STRAND CONSTRUCTION

Fiber Content

- High Tenacity Polypropylene Fiber

Characteristics

- Higher strength than polypropylene
- Floats
- Superior ultraviolet resistance
- Excellent flex wear resistance
- Non-Torque construction

Applications

- Floating tow lines
- Mooring and tie-up lines
- Mooring pick-up lines

Dia		Cir	Weight		MBL	
inch	mm	inch	200m/kg	600ft/lb	ton	kN
1-1/8	28	3-1/2	78	158	15.20	149.20
1-1/4	32	4	101	204	19.50	191.40
1-7/16	36	4-1/2	128	258	25.00	245.40
1-9/16	40	5	158	319	30.00	294.20
1-3/4	44	5-1/2	195	392	36.00	353.00
1-7/8	48	6	229	462	43.00	421.70
2-1/16	52	6-1/2	268	541	48.50	475.60
2-1/4	56	7	312	629	55.50	544.30
2-3/8	60	7-1/2	359	724	65.00	637.40
2-1/2	64	8	407	821	72.00	706.10
2-7/8	72	9	515	1,039	91.00	892.40
3-5/32	80	10	638	1,286	111.00	1,088.50
3-7/16	88	11	772	1,556	135.00	1,323.90
3-13/16	96	12	916	1,847	158.00	1,549.50
4-1/8	104	13	1,071	2,158	185.00	1,814.20
4-7/16	112	14	1,245	2,510	214.00	2,098.60

• ± 5% tolerance according to ISO 2307

