




# Mega PS

## Structure



8-STRAND CONSTRUCTION

## Fiber Content

- Polyester Fiber

## Characteristics

- High strength and low stretch
- Excellent wear life
- Balanced, non-rotational construction
- Fast easy splicing

## Applications

- Mooring and Tie-up lines
- Mooring pendants
- For navy

Dia		Cir		Weight		MBL	
inch	mm	inch	200m/kg	600ft/lb	ton	kN	
1-1/8	28	3-1/2	119	240	16.00	156.90	
1-1/4	32	4	155	313	21.00	205.90	
1-7/16	36	4-1/2	196	396	26.00	255.00	
1-9/16	40	5	243	489	32.00	313.80	
1-3/4	44	5-1/2	294	592	38.00	372.70	
1-7/8	48	6	350	706	46.00	451.10	
2-1/16	52	6-1/2	410	827	54.00	529.60	
2-1/4	56	7	476	960	62.00	608.00	
2-3/8	60	7-1/2	546	1,101	73.00	715.90	
2-1/2	64	8	622	1,254	83.00	813.90	
2-7/8	72	9	786	1,585	103.00	1,010.10	
3-5/32	80	10	970	1,955	127.00	1,245.40	
3-7/16	88	11	1,174	2,366	152.00	1,490.60	
3-13/16	96	12	1,398	2,818	181.00	1,775.00	
4-1/8	104	13	1,640	3,306	208.00	2,039.80	
4-7/16	112	14	1,900	3,830	243.00	2,383.00	

• ± 5% tolerance according to ISO 2307

