


Tera NY



Structure



12-STRAND CONSTRUCTION

Fiber Content

- Nylon Fiber

Characteristics

- Excellent shock mitigation
- Superior strength
- Maintains high service life flexibility
- Non-Torquing
- Fast, Easy splicing

Applications

- Anchor lines
- Deep water mooring lines
- Specialty slings
- Tow lines

Dia		Cir		Weight		MBL	
inch	mm	inch	200m/kg	600ft/lb	ton	kN	
1-9/16	40	5	198	400	37.00	362.80	
1-3/4	44	5-1/2	240	484	44.00	431.50	
1-7/8	48	6	284	572	50.00	490.30	
2-1/16	52	6-1/2	332	669	59.00	578.60	
2-1/4	56	7	400	806	71.00	696.30	
2-3/8	60	7-1/2	445	898	79.00	774.70	
2-1/2	64	8	504	1,015	90.00	882.60	
2-7/8	72	9	660	1,330	115.00	1,127.80	
3-5/32	80	10	800	1,613	138.00	1,353.30	
3-7/16	88	11	954	1,922	160.00	1,569.10	
3-13/16	96	12	1,136	2,291	191.00	1,873.10	
4-1/8	104	13	1,332	2,685	212.00	2,079.00	
4-7/16	112	14	1,544	3,112	230.00	2,255.50	
4-3/4	120	15	1,773	3,574	270.00	2,647.80	

• ± 5% tolerance according to ISO 2307

