


# Tera PS



## Structure



12-STRAND CONSTRUCTION

## Fiber Content

● Polyester Fiber

## Characteristics

- Low stretch
- Non-torquing Non-rotational
- Excellent abrasion resistance
- Fast, Easy splicing

## Applications

- Pulling lines
- Deep water mooring lines
- Specialty slings
- Tow lines

	Dia		Cir	Weight		MBL	
	inch	mm		200m/kg	600ft/lb	ton	kN
1-9/16		40	5	243	489	34.00	333.40
1-3/4		44	5-1/2	294	592	39.00	382.50
1-7/8		48	6	350	706	47.00	460.90
2-1/16		52	6-1/2	410	824	56.00	549.20
2-1/4		56	7	476	960	64.00	627.60
2-3/8		60	7-1/2	546	1,101	76.00	745.30
2-1/2		64	8	622	1,254	84.00	823.80
2-7/8		72	9	786	1,585	109.00	1,068.90
3-5/32		80	10	970	1,955	133.00	1,304.30
3-7/16		88	11	1,174	2,366	159.00	1,559.30
3-13/16		96	12	1,395	2,818	191.00	1,873.10
4-1/8		104	13	1,640	3,306	221.00	2,167.30
4-7/16		112	14	1,900	3,830	256.00	2,510.50
4-3/4		120	15	2,180	4,395	293.00	2,873.30

• ± 5% tolerance according to ISO 2307

