


TeraFlex

Structure



12-STRAND CONSTRUCTION

Fiber Content

- Polyester & High Tenacity Polypropylene Fiber Mixed

Characteristics

- Excellent wear life
- High strength, Low stretch
- Non-Rotating and Easily spliced

Applications

- Tug assist lines
- Mooring and pendant lines
- Barge tie-up lines

Dia		Cir	Weight		MBL	
inch	mm	inch	200m/kg	600ft/lb	ton	kN
1-9/16	40	5	182	367	34.00	333.40
1-3/4	44	5-1/2	218	440	40.00	392.30
1-7/8	48	6	264	531	47.00	460.90
2-1/16	52	6-1/2	300	605	54.00	529.60
2-1/4	56	7	357	720	64.00	627.60
2-3/8	60	7-1/2	401	808	72.00	706.10
2-1/2	64	8	452	911	81.00	794.30
2-7/8	72	9	567	1,144	102.00	1,000.30
3-5/32	80	10	696	1,404	124.00	1,216.00
3-7/16	88	11	840	1,693	148.00	1,451.40
3-13/16	96	12	1,000	2,016	175.00	1,716.20
4-1/8	104	13	1,164	2,345	202.00	1,980.90
4-7/16	112	14	1,345	2,712	233.00	2,284.90
4-3/4	120	15	1,549	3,122	266.00	2,608.60

• ± 5% tolerance according to ISO 2307

