

Manho PP Mono 3 Strand Rope

Length : 200m

SIZE			PP MONO		
Dia (mm)	Dia (inch)	Circ (inch)	Weight (kg)	M.B.L (ton)	
				M-Lay	MS-Lay
3	1/8	3/8	0.85	0.14	0.17
4	5/32	1/2	1.50	0.22	0.27
5	3/16	5/8	2.30	0.34	0.42
6	1/4	3/4	3.50	0.50	0.62
7	9/32	7/8	4.75	0.67	0.84
8	5/16	1	6.20	0.85	1.10
9	3/8	1-1/8	7.80	1.06	1.32
10	13/32	1-1/4	9.60	1.29	1.57
11	7/16	1-3/8	11.7	1.54	1.90
12	15/32	1-1/2	13.9	1.80	2.23
13	1/2	1-5/8	16.3	2.11	2.62
14	9/16	1-3/4	18.8	2.40	3.05
16	5/8	2	24.2	3.00	3.77
18	23/32	2-1/4	30.8	3.80	4.81
19	3/4	2-3/8	34.0	4.20	5.30
20	13/16	2-1/2	38.0	4.50	5.80
22	7/8	2-3/4	46.0	5.60	6.95
24	15/16	3	54.7	6.50	8.13
25	1	3-1/8	59.2	7.00	8.80
26	1-1/32	3-1/4	63.8	7.50	9.40
28	1-1/8	3-1/2	73.6	8.50	10.7
30	1-3/16	3-3/4	85.2	9.90	12.2
32	1-1/4	4	96.7	11.0	13.5
34	1-1 1/32	4-1/4	110.0	12.4	15.4
36	1-7/16	4-1/2	122.0	13.7	16.9
38	1-1/2	4-3/4	135.0	15.1	18.7
40	1-19/32	5	152.0	16.7	20.5
42	1-21/32	5-1/4	167.0	18.5	22.5
45	1-25/32	5-5/8	191.0	20.7	25.0
48	1-7/8	6	218.0	23.6	28.6
50	2	6-1/4	236.0	25.5	31.0
55	2-5/32	6-7/8	286.0	30.0	36.5
56	2-1/4	7	296.0	31.0	37.8
60	2-3/8	7-1/2	340.0	35.5	43.3
64	2-1/2	8	387.0	40.0	49.0
65	2-9/16	8-1/8	399.0	41.0	50.5
72	2-7/8	9	490.0	50.3	61.5
80	3-5/32	10	605.0	60.5	75.6
85	3-11/32	10-1/2	683.0	68.0	85.3
90	3-9/16	11-1/8	765.0	75.0	95.5
96	3-25/32	12	871.0	84.7	107.0
100	3-15/16	12-3/8	945.0	91.5	116.0

NOTE:

- The above table is based on Manho standards, length and lay can be adjustable according to request.
- Please contact us if needed higher breaking load than above table as this minimum breaking load can be variable according to lay hardness.
- M-Lay : Medium lay
- MS-Lay : Medium Soft lay
- M.B.L : Minimum Breaking Load
- Ton : Metric Ton