



Type	Colourcode according to Euronorm	W.L.L. (kg)	webbing width (mm)	Number of layers	D-fitting						
					D (mm)	E (mm)	H (mm)	L (mm)	P (mm)	S (mm)	Ø (mm)
MCDD 30	Purple	1.000	30	2	45	70	60	-	-	30	12
MCDD 60	Green	2.000	60	2	30	100	80	-	-	60	16
MCDD 90	Yellow	3.000	90	2	60	146	120	-	-	90	20
MCDD 120	Grey	4.000	120	2	60	179	130	-	-	120	23
MCDD 150	Red	5.000	150	2	90	222	180	-	-	150	26
MCDD 180	Brown	6.000	180	2	90	262	180	-	-	180	28
MCDD 240	Blue	8.000	240	2	100	344	200	-	-	240	32
MCDD 300	Orange	10.000	300	2	100	400	250	-	-	300	35
					DS-fitting						
					D (mm)	E (mm)	H (mm)	L (mm)	P (mm)	S (mm)	Ø (mm)
MCDDS 30	Purple	1.000	30	2	50	-	80	80	25	30	12
MCDDS 60	Green	2.000	60	2	40	-	115	115	40	60	16
MCDDS 90	Yellow	3.000	90	2	70	-	160	160	55	90	20
MCDDS 120	Grey	4.000	120	2	80	-	200	200	55	120	23
MCDDS 150	Red	5.000	150	2	90	-	240	240	80	150	26
MCDDS 180	Brown	6.000	180	2	90	-	284	284	80	180	28
MCDDS 240	Blue	8.000	240	2	120	-	370	370	90	240	32
MCDDS 300	Orange	10.000	300	2	120	-	424	424	100	300	35

MCDD en MCDDS polyester lifting slings with metal endfittings

Details

- In accordance with Machine Directive 98/37/EC (last amendment 98/79/EC).
- Double ply lifting sling.
- Color-coding in accordance with DIN-EN 1492-1.
- Stripe-code: each stripe is equal to one tonne capacity.
- MC = Multicode.
- Extra pre-impregnated webbing for a high abrasion resistance.
- Low elongation.

